LITHEAUDIO

4" HOTEL BLUETOOTH **CEILING SPEAKER**

ELEVATE THE GUEST EXPERIENCE




EASY AS CONNECT & STREAM


The Lithe 4" Bluetooth Ceiling Speaker has a compact, sleek and unobtrusive design which blends seamlessly into any hotel decor while delivering outstanding sound that will elevate any hotel rooms guest listening experience. This cutting-edge all-in-one audio solution is perfect for adding audio to bathrooms, bedrooms, hotels spas and lodges. Included is volume capping, password protection and speaker naming.















Speaker Spec

4" Inch PP Woofer Cone

0.75 Inch Silk Tweeter

Impedance: 8 Ohms

RMS Power: 25W RMS

Sensitivity (1W/1M): 88dB

Audio Sample Rate: 48Khz

50% Volume Capping Switch

USB For Firmware Updates

Stereo / Mono Switch

Bluetooth 5.0

3.5mm Line-In

Sound Quality: THD+N 0.009%, 70Hz - 20kHz



OPEN YOUR PHONE CAMERA & SCAN THE QR CODE FOR AUGMENTED REALITY





SUITABLE FOR BATHROOMS also ideal for garden rooms



for areas you want to ensure volume is not turned up



PASSWORD PROTECTED

Ensure your neighbours cannot connect to your speaker

PERFECT FOR

Bathrooms Bedrooms

Garden rooms

Home office


Hotel rooms

Holiday lodges

ROOM XX

RENAME EACH SPEAKER

to make identifying the speaker



MAINTENANCE FRIENDLY Just add power. Everything else you need is built in.

SPECIFICATIONS / FEATURES

Features

Full Room Connectivity

Latest Bluetooth 5.0 technology built-in

All-In-One Solution

Amplifier & Bluetooth built-in, so all you need is power

Designed for smaller rooms and hospitality

Perfect for Bathrooms, bedrooms, hotels, lodges, gyms & spas

Amplifier Built-In

werful 25W RMS Class D Amplifier

Volume Cap 50%

Control your audio with the volume capping feature

Use the Lithe setup app to configure your speakers

Pin Change

Password Protected

IP44 Rated for Bathrooms Water-resistant, making them ideal for bathrooms

High-Quality Audio

Delivering superb sound quality with pin sharp clarity

Connect to TV 3.5mm Jack Input

Easy Installation

Connect to plug socket or existing lighting circuit

Frameless Protective Metal Grille

Dimensions: (H X W) 186 X 83mm (7.3 x 3.3 inch)

Power Input Supply: 100 - 240V~ 50/60Hz

Transformer Output Supply: DC24V / 2.5A

Operating Temperature: 0° to 40°C

Storage Temperature: -20° to 70°C

Hole cut out: 165mm diameter

IP44 Rated as standard

Weight 1.0kg (2.2 lbs)

Connectivity

Works with any Bluetooth device

Wireless Range: Up to 30 metres (Bluetooth V5.0 devices)

Works with Ok Google

Works with Alexa

Line in (AUX input)

Output for additional Passive Speaker

Bluetooth Setup App for Android and IOS

Lithe Sub (via Alexa)

What's in the box

4" Bluetooth Ceiling Speaker

Power Supply

Cutting Template Instruction Manual

Pair kit also includes:

4" Passive Ceiling Speaker

5m Speaker Cable

SKU Codes

03250 4" Master Bluetooth Ceiling Speaker

03255 4" Passive Ceiling Speaker

03260 4" Bluetooth & Passive Ceiling Speaker Bundle (Pair kit inc 5M speaker cable)