



Quantity	Value
Physical	
Size (HxWxD):	37x42x16 mm / 1.46x1.65x0.63 inch
Weight:	<ul style="list-style-type: none"><li>EM Gen3 - 23 g / 0.81 oz</li><li>CT 50A - 50 g / 1.76 oz</li></ul>
Screw terminals max torque:	0.4 Nm / 3.5 lbin
Conductor cross section:	0.2 to 2.5 mm <sup>2</sup> / 24 to 14 AWG (solid, stranded, and bootlace ferrules)
Conductor stripped length:	6 to 7 mm / 0.24 to 0.28 in
Mounting:	Wall console, Electrical cabinet
Shell material:	Plastic
Shell color:	<ul style="list-style-type: none"><li>White</li><li>Charcoal gray</li></ul>
Connectors color:	Black
Environmental	
Ambient working temperature:	-20 °C to 40 °C / -5 °F to 105 °F
Humidity:	30 % to 70 % RH
Max. altitude:	3000 m / 9842 ft

Shelly EM Gen3	
Quantity	Value
Physical	
Size (HxWxD):	37x42x16 mm / 1.46x1.65x0.63 inch
Weight:	<ul style="list-style-type: none"><li>EM Gen3 - 23 g / 0.81 oz</li><li>CT 50A - 50 g / 1.76 oz</li></ul>
Screw terminals max torque:	0.4 Nm / 3.5 lbin
Conductor cross section:	0.2 to 2.5 mm <sup>2</sup> / 24 to 14 AWG (solid, stranded, and bootlace ferrules)
Conductor stripped length:	6 to 7 mm / 0.24 to 0.28 in
Mounting:	Wall console, Electrical cabinet
Shell material:	Plastic
Shell color:	<ul style="list-style-type: none"><li>White</li><li>Charcoal gray</li></ul>
Connectors color:	Black
Environmental	
Ambient working temperature:	-20 °C to 40 °C / -5 °F to 105 °F
Humidity:	30 % to 70 % RH
Max. altitude:	3000 m / 9842 ft

Shelly EM Gen3	
Quantity	Value
Physical	
Size (HxWxD):	37x42x16 mm / 1.46x1.65x0.63 inch
Weight:	<ul style="list-style-type: none"><li>EM Gen3 - 23 g / 0.81 oz</li><li>CT 50A - 50 g / 1.76 oz</li></ul>
Screw terminals max torque:	0.4 Nm / 3.5 lbin
Conductor cross section:	0.2 to 2.5 mm² / 24 to 14 AWG (solid, stranded, and bootlace ferrules)
Conductor stripped length:	6 to 7 mm / 0.24 to 0.28 in
Mounting:	Wall console, Electrical cabinet
Shell material:	Plastic
Shell color:	<ul style="list-style-type: none"><li>White</li><li>Charcoal gray</li></ul>
Connectors color:	Black
Environmental	
Ambient working temperature:	-20 °C to 40 °C / -5 °F to 105 °F
Humidity:	30 % to 70 % RH
Max. altitude:	3000 m / 9842 ft

Shelly EM Gen3	
Quantity	Value
Physical	
Size (HxWxD):	37x42x16 mm / 1.46x1.65x0.63 inch
Weight:	<ul style="list-style-type: none"><li>EM Gen3 - 23 g / 0.81 oz</li><li>CT 50A - 50 g / 1.76 oz</li></ul>
Screw terminals max torque:	0.4 Nm / 3.5 lbin
Conductor cross section:	0.2 to 2.5 mm <sup>2</sup> / 24 to 14 AWG (solid, stranded, and bootlace ferrules)
Conductor stripped length:	6 to 7 mm / 0.24 to 0.28 in
Mounting:	Wall console, Electrical cabinet
Shell material:	Plastic
Shell color:	<ul style="list-style-type: none"><li>White</li><li>Charcoal gray</li></ul>
Connectors color:	Black
Environmental	
Ambient working temperature:	-20 °C to 40 °C / -5 °F to 105 °F
Humidity:	30 % to 70 % RH
Max. altitude:	3000 m / 9842 ft

Shelly EM Gen3	
Quantity	Value
Physical	
Size (HxWxD):	37x42x16 mm / 1.46x1.65x0.63 inch
Weight:	<ul style="list-style-type: none"><li>EM Gen3 - 23 g / 0.81 oz</li><li>CT 50A - 50 g / 1.76 oz</li></ul>
Screw terminals max torque:	0.4 Nm / 3.5 lbin
Conductor cross section:	0.2 to 2.5 mm <sup>2</sup> / 24 to 14 AWG (solid, stranded, and bootlace ferrules)
Conductor stripped length:	6 to 7 mm / 0.24 to 0.28 in
Mounting:	Wall console, Electrical cabinet
Shell material:	Plastic
Shell color:	<ul style="list-style-type: none"><li>White</li><li>Charcoal gray</li></ul>
Connectors color:	Black
Environmental	
Ambient working temperature:	-20 °C to 40 °C / -5 °F to 105 °F
Humidity:	30 % to 70 % RH
Max. altitude:	3000 m / 9842 ft

Shelly EM Gen3	
Quantity	Value
Physical	
Size (HxWxD):	37x42x16 mm / 1.46x1.65x0.63 inch
Weight:	<ul style="list-style-type: none"><li>EM Gen3 - 23 g / 0.81 oz</li><li>CT 50A - 50 g / 1.76 oz</li></ul>
Screw terminals max torque:	0.4 Nm / 3.5 lbin
Conductor cross section:	0.2 to 2.5 mm² / 24 to 14 AWG (solid, stranded, and bootlace ferrules)
Conductor stripped length:	6 to 7 mm / 0.24 to 0.28 in
Mounting:	Wall console, Electrical cabinet
Shell material:	Plastic
Shell color:	<ul style="list-style-type: none"><li>White</li><li>Charcoal gray</li></ul>
Connectors color:	Black
Environmental	
Ambient working temperature:	-20 °C to 40 °C / -5 °F to 105 °F
Humidity:	30 % to 70 % RH
Max. altitude:	3000 m / 9842 ft

Shelly EM Gen3	
Quantity	Value
Physical	
Size (HxWxD):	37x42x16 mm / 1.46x1.65x0.63 inch
Weight:	<ul style="list-style-type: none"><li>EM Gen3 - 23 g / 0.81 oz</li><li>CT 50A - 50 g / 1.76 oz</li></ul>
Screw terminals max torque:	0.4 Nm / 3.5 lbin
Conductor cross section:	0.2 to 2.5 mm <sup>2</sup> / 24 to 14 AWG (solid, stranded, and bootlace ferrules)
Conductor stripped length:	6 to 7 mm / 0.24 to 0.28 in
Mounting:	Wall console, Electrical cabinet
Shell material:	Plastic
Shell color:	<ul style="list-style-type: none"><li>White</li><li>Charcoal gray</li></ul>
Connectors color:	Black
Environmental	
Ambient working temperature:	-20 °C to 40 °C / -5 °F to 105 °F
Humidity:	30 % to 70 % RH
Max. altitude:	3000 m / 9842 ft

Shelly EM Gen3	
Quantity	Value
Physical	
Size (HxWxD):	37x42x16 mm / 1.46x1.65x0.63 inch
Weight:	<ul style="list-style-type: none"><li>EM Gen3 - 23 g / 0.81 oz</li><li>CT 50A - 50 g / 1.76 oz</li></ul>
Screw terminals max torque:	0.4 Nm / 3.5 lbin
Conductor cross section:	0.2 to 2.5 mm² / 24 to 14 AWG (solid, stranded, and bootlace ferrules)
Conductor stripped length:	6 to 7 mm / 0.24 to 0.28 in
Mounting:	Wall console, Electrical cabinet
Shell material:	Plastic
Shell color:	<ul style="list-style-type: none"><li>White</li><li>Charcoal gray</li></ul>
Connectors color:	Black
Environmental	
Ambient working temperature:	-20 °C to 40 °C / -5 °F to 105 °F
Humidity:	30 % to 70 % RH
Max. altitude:	3000 m / 9842 ft



Shelly EM Gen3	
Quantity	Value
Physical	
Size (HxWxD):	37x42x16 mm / 1.46x1.65x0.63 inch
Weight:	<ul style="list-style-type: none"><li>EM Gen3 - 23 g / 0.81 oz</li><li>CT 50A - 50 g / 1.76 oz</li></ul>
Screw terminals max torque:	0.4 Nm / 3.5 lbin
Conductor cross section:	0.2 to 2.5 mm <sup>2</sup> / 24 to 14 AWG (solid, stranded, and bootlace ferrules)
Conductor stripped length:	6 to 7 mm / 0.24 to 0.28 in
Mounting:	Wall console, Electrical cabinet
Shell material:	Plastic
Shell color:	<ul style="list-style-type: none"><li>White</li><li>Charcoal gray</li></ul>
Connectors color:	Black
Environmental	
Ambient working temperature:	-20 °C to 40 °C / -5 °F to 105 °F
Humidity:	30 % to 70 % RH
Max. altitude:	3000 m / 9842 ft

Shelly EM Gen3	
Quantity	Value
Physical	
Size (HxWxD):	37x42x16 mm / 1.46x1.65x0.63 inch
Weight:	<ul style="list-style-type: none"><li>EM Gen3 - 23 g / 0.81 oz</li><li>CT 50A - 50 g / 1.76 oz</li></ul>
Screw terminals max torque:	0.4 Nm / 3.5 lbin
Conductor cross section:	0.2 to 2.5 mm² / 24 to 14 AWG (solid, stranded, and bootlace ferrules)
Conductor stripped length:	6 to 7 mm / 0.24 to 0.28 in
Mounting:	Wall console, Electrical cabinet
Shell material:	Plastic
Shell color:	<ul style="list-style-type: none"><li>White</li><li>Charcoal gray</li></ul>
Connectors color:	Black
Environmental	
Ambient working temperature:	-20 °C to 40 °C / -5 °F to 105 °F
Humidity:	30 % to 70 % RH
Max. altitude:	3000 m / 9842 ft

Shelly EM Gen3	
Quantity	Value
Physical	
Size (HxWxD):	37x42x16 mm / 1.46x1.65x0.63 inch
Weight:	<ul style="list-style-type: none"><li>EM Gen3 - 23 g / 0.81 oz</li><li>CT 50A - 50 g / 1.76 oz</li></ul>
Screw terminals max torque:	0.4 Nm / 3.5 lbin
Conductor cross section:	0.2 to 2.5 mm <sup>2</sup> / 24 to 14 AWG (solid, stranded, and bootlace ferrules)
Conductor stripped length:	6 to 7 mm / 0.24 to 0.28 in
Mounting:	Wall console, Electrical cabinet
Shell material:	Plastic
Shell color:	<ul style="list-style-type: none"><li>White</li><li>Charcoal gray</li></ul>
Connectors color:	Black
Environmental	
Ambient working temperature:	-20 °C to 40 °C / -5 °F to 105 °F
Humidity:	30 % to 70 % RH
Max. altitude:	3000 m / 9842 ft

Shelly EM Gen3	
Quantity	Value
Physical	
Size (HxWxD):	37x42x16 mm / 1.46x1.65x0.63 inch
Weight:	<ul style="list-style-type: none"><li>EM Gen3 - 23 g / 0.81 oz</li><li>CT 50A - 50 g / 1.76 oz</li></ul>
Screw terminals max torque:	0.4 Nm / 3.5 lbin
Conductor cross section:	0.2 to 2.5 mm <sup>2</sup> / 24 to 14 AWG (solid, stranded, and bootlace ferrules)
Conductor stripped length:	6 to 7 mm / 0.24 to 0.28 in
Mounting:	Wall console, Electrical cabinet
Shell material:	Plastic
Shell color:	<ul style="list-style-type: none"><li>White</li><li>Charcoal gray</li></ul>
Connectors color:	Black
Environmental	
Ambient working temperature:	-20 °C to 40 °C / -5 °F to 105 °F
Humidity:	30 % to 70 % RH
Max. altitude:	3000 m / 9842 ft