



Overheating protection



Overpower protection



Overvoltage protection



Flame protection

Specifications

Power supply	110 - 240 V ~, 50/60 Hz
Power consumption	< 0.3W
Power measurement	Yes
Overheating protection	Yes
External protection	10 A, tripping characteristic
B OR C, 6 KA INTERRUPTING RATING, ENERGY LIMITING CLASS 3	
Dimming type	Trailing edge
Max. Output power	200 W
Overload protection	Yes
Overvoltage protection	Yes
Distance	Up to 40 m indoors (131 ft.) (depends on local condition)
Z-Wave® repeater:	Yes
CPU	Z-Wave® S800
Z-Wave® frequency bands	868.4 MHz

Size (H x W x D)	94 × 19 × 69 ±0.5 mm / 3.7 × 0.75 x 2.71 ±0.02 in
Weight	75 g / 2.65 oz.
Mounting	DIN rail
Screw terminals max. torque	0.4 Nm / 3.54 lbin
Conductor cross section	0.5 to 2.5 mm ² / 20 to 14 AWG (green connectors)
	0.5 to 1.5 mm ² / 20 to 16 AWG (white connectors)
Conductor stripped length	6 to 7 mm / 0.24 to 0.28 in (green connector)
	5 to 6 mm / 0.20 to 0.24 in (white connectors) (solid, stranded, and bootlace ferrules)
Shell material	Plastic
Color	Lime
Ambient temperature	-20°C to 40°C / -5°F to 105°F
Humidity	30% to 70% RH
Max. altitude	2000 m / 6562 ft.