

This website uses cookies to improve website navigation, analyze online activities and have the best possible user experience on our website. You can object to the use of cookies at any time. You can find more information in our [privacy policy](#) .

Cookie Settings

Accept All Cookies



TL-SG2218P
JetStream 18-Port Gigabit Smart Switch with 16-Port PoE+

Buy Now

HARDWARE FEATURES

Standards and Protocols	IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE802.3z, IEEE 802.3ad, IEEE 802.3x, IEEE 802.3az, IEEE 802.1d, IEEE 802.1s, IEEE 802.1w, IEEE 802.1q, IEEE 802.1p, IEEE 802.1x
Interface	<ul style="list-style-type: none">• 16× 10/100/1000 Mbps RJ45 Ports (Auto Negotiation/Auto MDI/MDIX)• 2× Gigabit SFP Slots
Network Media	<ul style="list-style-type: none">• 10BASE-T: UTP category 3, 4, 5 cable (maximum 100m)• 100BASE-TX/1000Base-T: UTP category 5, 5e or above cable (maximum 100m)• 1000BASE-X: MMF, SMF
Fan Quantity	1
Power Supply	100-240V AC, 50/60Hz
PoE Ports (RJ45)	<ul style="list-style-type: none">• Standard: 802.3at/af compliant• PoE+ Ports: 16 Ports• PoE Power Budget: 150 W*
Dimensions (W x D x H)	17.3 × 7.1 × 1.7 in. (440 × 180 × 44 mm)
Mounting	Rack Mountable
Max Power Consumption	<ul style="list-style-type: none">• 181.4 W (110 V/60 Hz) (with 150 W PD connected)• 178.3 W (220 V/50 Hz) (with 150 W PD connected)
Max Heat Dissipation	<ul style="list-style-type: none">• 619.06 BTU/hr (110 V/60 Hz) (with 150 W PD connected)• 608.52 BTU/hr (220 V/50 Hz) (with 150 W PD connected)

PERFORMANCE

Switching Capacity	36 Gbps
Packet Forwarding Rate	26.78 Mpps
MAC Address Table	8K
Packet Buffer Memory	4.1 Mbit
Jumbo Frame	9 KB

SOFTWARE FEATURES

Quality of Service	<ul style="list-style-type: none">• 802.1p CoS/DSCP priority• 8 priority queues• Priority Schedule Mode<ul style="list-style-type: none">- SP (Strict Priority)- WRR (Weighted Round Robin)• Queue Weight Config• Bandwidth Control<ul style="list-style-type: none">- Port/Flow based Rating Limit
--------------------	--

SOFTWARE FEATURES

	<ul style="list-style-type: none">• Smoother Performance• Storm Control<ul style="list-style-type: none">- Multiple Control Modes(kbps/ratio)- Broadcast/Multicast/Unknown-Unicast Control
L2 and L2+ Features	<ul style="list-style-type: none">• 16 IP Interfaces<ul style="list-style-type: none">- Support IPv4/IPv6 Interface• Static Routing<ul style="list-style-type: none">- 32 IPv4/IPv6 Static Routes• DHCP Server• DHCP Relay<ul style="list-style-type: none">- DHCP Interface Relay- DHCP VLAN Relay• DHCP L2 Relay• Static ARP• Proxy ARP• Gratuitous ARP• Link Aggregation<ul style="list-style-type: none">- Static link aggregation- 802.3ad LACP- Up to 8 aggregation groups and up to 8 ports per group• Spanning Tree Protocol<ul style="list-style-type: none">- 802.1D STP- 802.1w RSTP- 802.1s MSTP- STP Security: TC Protect, BPDU Filter/Protect, Root Protect• Loopback Detection• Flow Control<ul style="list-style-type: none">- 802.3x Flow Control• Mirroring<ul style="list-style-type: none">- Port Mirroring- CPU Mirroring- One-to-One- Many-to-One- Flow-Based- Ingress/Egress/Both• Device Link Detect Protocol (DLDP)• 802.1ab LLDP/ LLDP-MED
Advanced Features	<ul style="list-style-type: none">• Automatic Device Discovery• Batch Configuration• Batch Firmware Upgrading• Intelligent Network Monitoring• Abnormal Event Warnings• Unified Configuration• Reboot Schedule
VLAN	<ul style="list-style-type: none">• VLAN Group<ul style="list-style-type: none">- Max. 4K VLAN Groups• 802.1Q tag VLAN• MAC VLAN: 12 Entries• Protocol VLAN

SOFTWARE FEATURES

	<ul style="list-style-type: none">• GVRP• Voice VLAN
Access Control List	<ul style="list-style-type: none">• Support up to 230 entries• Time-Range<ul style="list-style-type: none">- Time Slice- Week Time-Range- Absolute Time-Range- Holiday• Time-based ACL• MAC ACL<ul style="list-style-type: none">- Source MAC- Destination MAC- VLAN ID- User Priority- Ether Type• IP ACL<ul style="list-style-type: none">- Source IP- Destination IP- IP Protocol- TCP Flag- TCP/UDP Source Port- TCP/UDP Destination Port- DSCP/IP TOS• IPv6 ACL• Combined ACL• Rule Operation<ul style="list-style-type: none">- Permit/Deny• Policy Action<ul style="list-style-type: none">- Mirror- Rate Limit- Redirect- QoS Remark• ACL Rules Binding<ul style="list-style-type: none">- Port Binding- VLAN Binding• Actions for flows<ul style="list-style-type: none">- Mirror (to supported interface)- Redirect (to supported interface)- Rate Limit- QoS Remark
Security	<ul style="list-style-type: none">• AAA• 802.1X<ul style="list-style-type: none">- Port based authentication- MAC (Host) based authentication- Authentication Method includes PAP/EAP-MD5- MAB- Guest VLAN- Support Radius authentication and accountability• IP/IPv6-MAC Binding<ul style="list-style-type: none">- 512 Binding Entries- DHCP Snooping- DHCPv6 Snooping

SOFTWARE FEATURES

	<ul style="list-style-type: none">- ARP Inspection- ND Detection• IP Source Guard- 253 Entries- Source IP+Source MAC• IPv6 Source Guard- 183 Entries- Source IPv6 Address+Source MAC• DoS Defend• Static/Dynamic/Permanent Port Security- Up to 64 MAC addresses per port• Broadcast/Multicast/Unicast Storm Control- kbps/ratio control mode• Port Isolation• Secure web management through HTTPS with SSLv3/TLS 1.2• Secure Command Line Interface (CLI) management with SSHv1/SSHv2• IP/Port/MAC based access control
IPv6	<ul style="list-style-type: none">• IPv6 Static Routing and ACL• IPv6 Dual IPv4/IPv6• IPv6 Interface• Multicast Listener Discovery (MLD) Snooping• IPv6 neighbor discovery (ND)• Path maximum transmission unit (MTU) discovery• Internet Control Message Protocol (ICMP) version 6• TCPv6/UDPv6• IPv6 applications- DHCPv6 Client- Ping6- Tracert6- Telnet(v6)- IPv6 SNMP- IPv6 SSH- IPv6 SSL- Http/Https- IPv6 TFTP
MIBs	<ul style="list-style-type: none">• MIB II (RFC1213)• Bridge MIB (RFC1493)• P/Q-Bridge MIB (RFC2674)• Radius Accounting Client MIB (RFC2620)• Radius Authentication Client MIB (RFC2618)• Remote Ping, Traceroute MIB (RFC2925)• Support TP-Link private MIBs• RMON MIB(RFC1757, rmon 1,2,3,9)

MANAGEMENT

Omada App	<p>Yes, through</p> <ul style="list-style-type: none">• Omada Cloud-Based Controller• OC300
-----------	--

MANAGEMENT	
	<ul style="list-style-type: none">• OC200• Omada Software Controller
Centralized Management	<ul style="list-style-type: none">• Omada Cloud-Based Controller• Omada Hardware Controller OC300• Omada Hardware Controller OC200• Omada Software Controller
Cloud Access	Yes, through <ul style="list-style-type: none">• Omada Cloud-Based Controller• OC300• OC200• Omada Software Controller
Zero-Touch Provisioning	Yes. Requiring the use of Omada Cloud-Based Controller
Management Features	<ul style="list-style-type: none">• Web-based GUI• Command Line Interface (CLI) through telnet• SNMPv1/v2c/v3• SNMP Trap/Inform• RMON (1,2,3,9 groups)• SDM Template• DHCP/BOOTP Client• Dual Image, Dual Configuration• CPU Monitoring• Cable Diagnostics• EEE• SNTP• System Log
OTHERS	
Certification	CE, FCC, RoHS
Package Contents	TL-SG2218P <ul style="list-style-type: none">• Power Cord• Installation Guide• Rackmount Kit• Rubber Feet
System Requirements	Microsoft® Windows® XP, Vista™ or Windows 7/8/10/11, MAC® OS, NetWare®, UNIX® or Linux.
Environment	<ul style="list-style-type: none">• Operating Temperature: 0–50 °C (32–122 °F);• Storage Temperature: -40–70 °C (-40–158 °F)• Operating Humidity: 10–90% RH non-condensing• Storage Humidity: 5–90% RH non-condensing

*PoE budget calculations are based on laboratory testing. Actual PoE power budget is not guaranteed and will vary as a result of client limitations and environmental factors.

**Zero-Touch Provisioning requires the use of Omada Cloud-Based Controller. Please go to [Omada Cloud-Based Controller Product List](#) to find all the models supported by Omada Cloud-Based Controller.

Sign up for news & offers

Email Address

Sign Up

Follow Us

About	Press	Where to Buy	Partners	Promotions
Technical Support	News	Online Stores	Partner Programme	
Corporate Profile	Awards	Retail	Network Site Survey	
About Us	Security Advisory	Distributors	Technology Library	
Sustainability	Blog	VAR Partner		
Contact Us				
Careers at TP-Link				
Privacy Policy				
Modern Slavery Act				

United Kingdom / English

Copyright © 2024 TP-LINK CORPORATION PTE. LTD. All rights reserved.