

Weight	Without mount: 1.4 kg (3 lb) With mount: 1.7 kg (3.8 lb)
Enclosure material	Aluminum, plastic
Mounting	Pole mount (Kit included)
Wind loading	550 N at 200 km/h (123.6 lbf at 125 mph)
Wind survivability	200 km/h (125 mph)

Hardware

Networking interface	(1) GbE RJ45 port
Power method	Passive PoE 2-pair (4, 5+; 7, 8 return)
Power supply	24V, 0.3A gigabit PoE adapter (Included)
Supported voltage range	20-27V DC
Max. power consumption	7W
Gain	26 dBi
LEDs	Power, Ethernet
ESD/EMP protection	Air/contact \pm 24kV
Channel sizes	PtP mode: 10/20/30/40/50/60/80 MHz PtMP mode: 10/20/30/40 MHz
Ambient operating temperature	-40 to 70° C (-40 to 158° F)
Ambient operating humidity	5 to 95% noncondensing
Certifications	CE, FCC, IC

Operating Frequency (MHz)

Worldwide	5150-5875 MHz
USA	
U-NII-1	5150-5250 MHz
U-NII-2A	5250-5350 MHz
U-NII-2C	5240-5725 MHz
U-NII-3	5725-5850 MHz

Management Radio (MHz)

Worldwide	2412 - 2472 MHz
US/CA	2412 - 2462 MHz

Stay in Touch

Email

Subscribe



[Terms and Conditions](#) | [Terms of Service](#) | [Privacy Policy](#) | [Return Policy](#) | [Cookies Settings](#)

© 2024 Ubiquiti Inc. All rights reserved.