



WiFi Switching Cloud Keys & Gateways Camera Security Door Access Power Tech New Integrations

New Integrations > [Analog Telephone Adapter](#)

Datasheet

In The Box

Marketing Images

Installation Guide

Supports up to two analog telephones and fax machines*



(3) Device control keys

Fax support using G.711 Power input



Headset functionality for the primary line



* Compatibility of other analog devices (e.g., fire alarm systems) is not guaranteed.

Mechanical

Dimensions

131.5 x 110.7 x 28.2 mm (5.2 x 4.4 x 1.1")

Weight

300 g (10.6 oz)

Enclosure material	Plastic
Mounting	Flat/angle mount

Display

Display size	86 mm (3.4") diagonal
Resolution	192 x 64 dots

Hardware

Memory	RAM: 128 Mb DDR3 Storage: 256 Mb
Power method	USB-C 5V DC, 1A PoE 48V DC, 0.35A
Power supply	5V DC, 1A power adapter, 1.5 m cord (included) PoE (pair B 4, 5+; 7, 8-)
Connectivity	(1) 100 MbE RJ45 port/PoE (1) 3.5 mm (0.14") headset port (2) RJ11 FXS ports (1) USB-C (power input) 802.11a/b/g/n/ac WiFi 2.4G b/g/n, BW 20 WiFi 5G a/n/ac, BW 20/40/80
Buttons	(3) Device control keys
Telephone features	Voicemail, DND, caller ID, call transfer, call waiting, 3-way conference
Ambient operating temperature	0 to 40° C (32 to 104° F)
Ambient operating humidity	10 to 90% noncondensing
Certifications	FCC, IC, CE

Software

Fax over IP	Fax pass-through using G.711
Voice codec	G.711 u/a
Number of supported phone lines	2

Software

Management application

UniFi Talk: Version 1.12.0 and later

Stay in Touch

 

[Terms and Conditions](#) | [Terms of Service](#) | [Privacy Policy](#) | [Return Policy](#) | [Cookies Settings](#)

© 2024 Ubiquiti, Inc. All rights reserved.